

TECHNONICOL CLEANER FOR PVC MEMBRANES

Description of material:

TechnoNICOL cleaner for PVC membranes – azeotrope blend of esters, ketones and alcohols. Cleaner activates and dries out surface of PVC membrane.

Application area:

TechnoNICOL cleaner for PVC membranes effectively removes organic residue (fats, bitumen, oil traces) and inorganic pollutants resulting from the installation and use of a polymer roofing. The cleaner is designed to remove local impurities from the surface of the LOGICROOF and ECOPLAST PVC-membranes. It is used for additional preparation of PVC-membrane surfaces for welding by hot air or a hot wedge.

Enhances the physical and mechanical properties of the welded seam.

Use for cleaning tools. The cleaner needs to be used before the additional sealing of seams with liquid PVC and when welding a new roof to the existing one.

Performance of works:

Wipe the contaminated areas of membrane with the white clear cloth. Do not pour cleaner directly on surface of membrane.

Surface coverage $V=S*0.00034$ (litres), S – square of roof.

Safety:

Avoid contact with eyes and skin. In case of contact with eyes, flush with large amounts of water and immediately consult the doctor. Apply in well-ventilated places. Keep away from children.

Storage:

Guaranteed shelf life in a dry cool protected from sun and frost place in original undamaged packaging – 24 months.

Transportation:

Product transported by all modes of transport in covered vehicles in accordance with the Rules of transportation of goods, operating in this type of transport.

Package:

Metallic can foil (3 kg).

