

TECHNONICOL CONTACT ADHESIVE LOGICROOF Bond

Description of material:

High-quality one-component polyurethane contact adhesive for manual gluing allows reliable glue joint without using a hardener.

Application area:

TechnoNICOL contact adhesive LOGICROOF Bond is used for adhesion of LOGICROOF FB with fleece backing to vertical surfaces of various roofing structures (to parapet walls, pipes, duct shafts, bitumen substrates, PIR panels with glass fiber facings etc.) made of metal, wood, concrete, stone, and other materials.

To facilitate the work signal coloring may be added in contact adhesive.

Surface coverage 1 liter per 4 m².

Performance of works:

Apply evenly on prepared surface with a roller.

After gluing membrane should be rolled on with a roller.

Polymerisation time is not more than 24 hours in normal operating conditions.

Do not apply near open flames. Avoid contact with eyes and skin.

Storage:

Store in a dry cool protected from sun and frost place in original undamaged packaging. Keep away from heat sources, sparks, open flames and direct sunrays. Storage temperatures +5°C...+30°C.

Warranty shelf life 12 months.

Transportation:

Product transported by all modes of transport in covered vehicles in accordance with the Rules of transportation of goods, operating in this type of transport.

Package:

Metallic can foil (10 liters).

